

Ravensberger Schmierstoffvertrieb GmbH
Postfach 1163
33819 Werther
Tel.: 05203/9719-0
Fax.: 05203/9719-40 / 41

- Certificate / ProductInformation-

RAVENOL MARINEOIL PETROL 25W-40 synthetic

Art. 1162115

Description:

RAVENOL MARINEOIL PETROL 25W-40 synthetic is an engine oil for the use in marine petrol engines.

RAVENOL MARINEOIL PETROL 25W-40 synthetic is produced with unconventional and HC basic oils, synthetic components and additives.

RAVENOL MARINEOIL PETROL 25W-40 synthetic guarantees longest oil change intervals and a high corrosion protection with a low oil and fuel consumption.

Quality classification:

RAVENOL MARINEOIL PETROL 25W-40 synthetic is tried and tested for aggregates specifying:

API SL

ACEA A3/B4

VETUS DEUTZ, Steyr, MTU, VOLVO PENTA, Caterpillar, IVECO, MAN, Mercruiser, PERKINS, NANNI Diesel, Yanmar, Detroit Diesel, SULZER, SKL

Technical characteristics:

RAVENOL MARINEOIL PETROL 25W-40 synthetic offers :

- excellent detergent and dispersant characteristics
- low evaporation
- high aging stability
- protection of reflecting surface formation
- very good cold start characteristics
- reduces oil and fuel consumption

Technical values:

Characteristics	unit	data	test according to	
Colour		blue		
Density	at 20 °C	kg/m ³	868	EN ISO 12185
Viscosity	at -25°C	mPas	<7000	DIN 51 377
	at 40 °C	mm ² /s	92,0	DIN 51 562
	at 100 °C	mm ² /s	13,7	DIN 51 562
Viscosity Index VI			151	DIN ISO 2909
Flash point	COC	°C	214	DIN ISO 2592
Pour point		°C	-36	DIN ISO 3016
Sulphated ash		%	1,3	DIN 51 575

All indicated data are approximate values and are subject to the commercial fluctuations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems occur please consult a technician.

28.03.13