- Certificate / ProductInformation-

RAVENOL RCS Racing Competition Synto SAE 5W-40

Art. 1141090

Description:

RAVENOL RCS Racing Competition Synto SAE 5W-40 is fully synthetic motor oil based on PAO and formulated with special esters for modern gasoline engines used for motor racing also by highest loading. High viscosity index and highly effective special additivation for use by extremely sporty driving style. Minimisation of friction, abrasion and fuel consumption, excellent cold start characteristics.

Application:

RAVENOL RCS Racing Competition Synto SAE 5W-40 is used as a special oil for racing under heaviest conditions.

Quality Classification: RAVENOL RCS Racing Competition Synto SAE 5W-40 corresponds to: Spezifikation: API SM/CF, ACEA A3/B4

Technical Characteristics:

RAVENOL RCS Racing Competition Synto SAE 5W-40 offers:

- Fuel savings in part-and full-load operation
- Very stable and excellent viscosity behavior
- Good shear stability
- Very good cold start properties
- Safe lubricating film with very high operating temperatures
- Excellent detergent and dispersant properties
- Protection against wear, corrosion and foaming

Technical Values:

Characteristics		unit	data	test according to
Colour			brown	visual
Density	at 20°C	kg/m³	846	DIN 51 757
Viscosity	at 40°C	mm²/s	89,3	DIN 51 562
-	at 100°C	mm²/s	14,1	DIN 51 562
Viscosity index VI			163	DIN ISO 2909
Flash point (COC)		°C	210	DIN ISO 2592
Pourpoint		°C	- 37	DIN ISO 3016
TBN		mg KOH/g	10,95	DIN ISO 3771
Sulphated ash		% wt.	1,0	

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service. 01.09.15