

- Certificate / ProductInformation -

RAVENOL RSS SAE 10W-60

Art. 1141100

RACING

Description:

RAVENOL RSS SAE 10W-60 is high alloyed fully synthetic multigrade engine oil for modern gasoline engines based on esters and poly-alpha olefins.

Special oil for use by car race, even under the heaviest loads. Its high viscosity index, its good shear stability and a highly effective special additive **RAVENOL RSS SAE 10W-60** is suitable for extremely sporty driving style. Secure lubrication, even at very high operating temperatures. Excellent protection against wear, corrosion and foam.

Application Directions:

RAVENOL RSS SAE 10W-60 can be used as special oil for car race even under most difficult conditions.

Quality Classification:

RAVENOL RSS SAE 10W-60 is tried and tested for aggregates specifying:

Specifications: API SN/CF, ACEA A3/B4

Recommendation: MB 229.1

Technical Characteristics:

RAVENOL RSS SAE 10W-60 offers:

- Fuel saving regarding partial load operation and full power operation
- Very stable and excellent viscosity behaviour
- Very good cold start characteristics
- Safe lubricating layer at very high operating temperatures
- Very good detergent and dispersant characteristics
- Good protection against corrosion and foam formation

Technical Values:

| Characteristics | unit | data | test according to | |
|---------------------------|-----------|--------------------|-------------------|--------------|
| Colour | | brown | visual | |
| Density | at 20 °C | kg/m ³ | 850 | EN ISO 12185 |
| Viscosity | at -25 °C | mPa*s | 5790 | ASTM D 5293 |
| | at 40 °C | mm ² /s | 155,59 | DIN 51 562 |
| | at 100 °C | mm ² /s | 22,11 | DIN 51 562 |
| Viscosity index VI | | 169 | | DIN ISO 2909 |
| Flash point (COC) | °C | 236 | | DIN ISO 2592 |
| Pour point | °C | - 36 | | DIN ISO 3016 |

All indicated data are approximate values and are subject to the commercial fluctuations.