Ravensberger Schmierstoffvertrieb GmbH Postfach 1163 33819 Werther

Tel.: 05203/9719-0 Fax.: 05203/9719-40 / 41

# - Certificate / ProductInformation -

#### **RAVENOL RRS SAE 5W-50**

Art. 1142100

**RACING** 

### **Description:**

**RAVENOL RRS SAE 5W-50** is synthetic multi-range engine oil which is produced on ester base oil and Poly-Alpha-Olefines.

Carefully chosen additives grant these high performance engine oil special characteristics. It can be used for different car racings for example DMV Tourenwagen Challenge.

#### **Application Directions:**

RAVENOL RRS SAE 5W-50 can be used as special oil for car racings even under most difficult conditions.

### **Quality Classification:**

RAVENOL RRS SAE 5W-50 is tried and tested for aggregates specifying:

Specification: API SN/CF, ACEA A3/B4

Recommendation: MB 229.1

#### **Technical Characteristics:**

## RAVENOL RRS SAE 5W-50 offers:

- Fuel saving regarding partial load operation and full power operation
- Very stable and excellent viscosity behaviour
- Good shear stability
- Very good cold start characteristics
- Safe lubricating layer at very high operating temperatures
- Very good detergent and dispersant characteristics
- Good protection against corrosion and foam formation

## **Technical Values:**

Characteristics		unit	data	test according to
Colour			brown	visual
Density	at 20 °C	kg/m³	853	EN ISO 12185
Viscosity	at - 30 °C	mPa*s	6500	ASTM D 5293
	at 40 °C	mm²/s	108,4	DIN 51 562
	at 100 °C	mm²/s	17,5	DIN 51 562
Viscosity index VI		178	DIN ISO 2909	
Flash point (COC)		°C	238	DIN ISO 2592
Pour point		°C	- 36	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.