Ravensberger Schmierstoffvertrieb GmbH Postfach 1163 33819 Werther

Tel.: 05203/9719-0 Fax.: 05203/9719-40 / 41

- Certificate / ProductInformation -

RAVENOL WATERCRAFT Fullsynth. 2-Takt

Art. 1151210

Description:

RAVENOL WATERCRAFT Fullsynth. 2-Takt is high quality blue coloured fully synthetic two-stroke engine oil. **RAVENOL WATERCRAFT Fullsynth. 2-Takt** with special esters and Polyisobutylene (PIB) and with effectively two stroke additives.

RAVENOL WATERCRAFT Fullsynth. 2-Takt is especially developes for two stroke engines in water vehicles.

Application Directions:

RAVENOL WATERCRAFT Fullsynth. 2-Takt can generally be mixed with regular petrol 1:100. RAVENOL WATERCRAFT Fullsynth. 2-Takt is used for lubrication of air-cooled two-stroke petrol engines with very high speed and heaviest load.

RAVENOL WATERCRAFT Fullsynth. 2-Takt is also suitable for the lubrication of two stroke scooters with water cooling.

Quality Classification:

RAVENOL WATERCRAFT Fullsynth. 2-Takt is approved, tried and tested for aggregates specifying:

Specifications: API TD, ISO-L EGD, Jaso FD Approval: NMMA TC-W3®, RL-29019G

Technical Characteristics:

RAVENOL WATERCRAFT Fullsynth. 2-Takt offers:

- A proper lubrication of all engine parts
- A strong cleaning effect, for clean combustion chambers. Cleans intake and exhaust ports from combustion residues and deposits
- Clean spark plugs provide optimal performance of the engines
- A very high wear and corrosion protection
- Low exhaust emission levels by good combustion

Technical Values:

Characteristics		unit	data	test according to
Colour			blue	visual
Density	at 20°C	kg/m³	869	EN ISO 12185
Viscosity	at 40°C	mm²/s	48,0	DIN 51 562
•	at 100°C	mm²/s	8,0	DIN 51 562
Viscosity index VI			138	DIN ISO 2909
Flash point	t (COC)	°C	110	DIN ISO 2592
Pour point	,	°C	- 21	DIN ISO 3016
TBN .		mg KOH/g	2,4	DIN ISO 3771
Sulphated ash		% wt.	<0,04	DIN 51 575

All indicated data are approximate values and are subject to the commercial fluctuations.