

Ravensberger Schmierstoffvertrieb GmbH
Postfach 1163
33819 Werther
Tel.: 05203/9719-0
Fax.: 05203/9719-40 / 41

- Certificate / ProductInformation -

RAVENOL SNOWMOBILES Teilsynth. 2-Takt

Art. 1152310

Description:

RAVENOL SNOWMOBILES Teilsynth. 2-Takt is high quality 2-stroke engine oil **with special esters and Polyisobutylene (PIB) and** an ash less additive package for optimum lubricity and excellent corrosion protection.

Application Directions:

RAVENOL SNOWMOBILES Teilsynth. 2-Takt is recommended for typical mixing ratio: 1: 75
RAVENOL SNOWMOBILES Teilsynth. 2-Takt is particularly suitable for the lubrication of air-cooled two-stroke gasoline engines with high speed and heavy load.
RAVENOL SNOWMOBILES Teilsynth. 2-Takt is ideal for lubricating two-stroke snowmobiles with suitable water cooling.

Quality Classification:

RAVENOL SNOWMOBILES Teilsynth. 2-Takt is approved, tried and tested for aggregates specifying:

Specifications: API TC, ISO-L-EGC

Approvals: JASO FC, Approval JASO 049RAV152

Recommendations: Yamaha, Suzuki, Bombardier, Kawasaki, Arctic Cat, Ski-Doo, Polaris.

Technical Characteristics:

RAVENOL SNOWMOBILES Teilsynth. 2-Takt offers:

- proper lubrication of all engine parts
- a strong cleaning effect, the combustion chambers and inlet and outlet ports freeing up largely of combustion residues and deposits
- clean spark plugs ensure optimal performance of the engines
- a very high wear and corrosion protection
- Low exhaust emissions through good combustion

Technical Values:

Characteristics		unit	data	test according to
Colour			blue	visual
Density	at 20°C	kg/m ³	868	EN ISO 12185
Viscosity	at 40°C	mm ² /s	35,9	DIN 51 562
	at 100°C	mm ² /s	6,29	DIN 51 562
Viscosity index VI			126	DIN ISO 2909
Flash point (COC)		°C	107	DIN ISO 2592
Pour point		°C	- 30	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

30.03.15