

Ravensberger Schmierstoffvertrieb GmbH
Postfach 1163
33819 Werther
Tel.: 05203/9719-0
Fax.: 05203/9719-40 / 41

- ProductInformation -

RAVENOL MARINEOIL DIESEL SHPD 10W-40 Art. 1162100

Description:

RAVENOL MARINEOIL DIESEL SHPD 10W-40 is a low friction engine oil for the use in marine diesel engines.

RAVENOL MARINEOIL DIESEL SHPD 10W-40 is produced with unconventional and HC basic oils, synthetic components and modern additives.

RAVENOL MARINEOIL DIESEL SHPD 10W-40 guarantees longest oil change intervals and a high corrosion protection with a low oil and fuel consumption.

Quality classification:

RAVENOL MARINEOIL DIESEL SHPD 10W-40 corresponds to :

API CI-4/CF

ACEA 2004 : E7/B4

Approvals : VETUS DEUTZ, Steyr, MTU, VOLVO PENTA, Caterpillar, IVECO, MAN, Mercruiser, PERKINS, NANNI Diesel, Yanmar, Detroit Diesel, SULZER, SKL

Technical characteristics:

- excellent detergent and dispersant characteristics
- low evaporation
- high aging stability
- protection of reflecting surface formation
- very good cold start characteristics
- reduces oil and fuel consumption

Technical values:

Characteristics		unit	data	test according to
Colour			blue	
Density	at 20°C	g/ml	0,868	DIN 51 757
Viscosity	at 40°C	mm ² /s	92,0	DIN 51 562
	at 100°C	mm ² /s	13,7	DIN 51 562
Viscosity index			151	DIN ISO 2909
Flashpoint	COC	°C	214	DIN ISO 2592
Pour point		°C	- 36	DIN ISO 3016
TBN		mg KOH/g	11	ISO 3771
Sulfated ash		%	1,3	

All indicated data are approximate values and are subject to the commercial fluctuations.