Ravensberger Schmierstoffvertrieb GmbH Postfach 1163

33819 Werther

Tel.: 05203/9719-0 Fax.: 05203/9719-40 / 41

- ProductInformation -

RAVENOL MARINEOIL PETROL SAE 25W-40

Art. 163220

Description:

RAVENOL MARINEOIL PETROL SAE 25W-40 is a modern high additive treated marine engine oil with synthetic additives. It is suitable for inboard and outboard marine gasoline engines. The high additive content guarantees an excellent effect on the detergent, dispersant and anti corrosion characteristics. It is a top quality product with high safety reserves.

Application directions:

RAVENOL MARINEOIL PETROL SAE 25W-40 is used in boat engines in case the specification SAE 25W-40 is requested.

Quality classification:

RAVENOL MARINEOIL PETROL SAE 25W-40 is practice-related and tested in aggregates with filling instructions:

- National Marine Manufacturers Association FC-W
- Yamaha; Honda; Suzuki
- Johnson; Mercury; Evenrude
- VOLVO Penta AB, Mercruiser, Yanmar, Kohler

Technical characteristics:

RAVENOL MARINEOIL PETROL SAE 25W-40 offers:

- suitability for catalysts
- excellent detergent and dispersant characteristics
- very good cold start characteristics
- a high oxidation stability
- an excellent viscosity temperature behaviour
- an excellent corrosion protection
- high safety reserves
- reduction of emissions

Technical values:

Characteristics		unit	data	test according to
Colour			blue	_
Density	at 20 ℃	g/ml	0,884	DIN 51 7 57
Viscosity	at 40 ℃	mm²/s	147,5	DIN 51 562
	at 100 ℃	mm²/s	17,5	DIN 51 562
Viscosity index			130	DIN ISO 2909
Flash point	t COC	\mathcal{C}	230	DIN ISO 2592
Pour point		\mathcal{C}	- 28	DIN ISO 3016
TBN		mg KOH/g	7,7-9,7	DIN ISO 3771
Sulfat ash		%	approx. 1,03	

All indicated data are approximate values and are subject to the commercial fluctuations.