Ravensberger Schmierstoffvertrieb GmbH Postfach 1163 33819 Werther

Tel.: 05203/9719-0 Fax.: 05203/9719-40 / 41

- ProductInformation -

RAVENOL Fork Oil Light 5W

Art. 182102

Description:

RAVENOL Fork Oil Light 5W is a fully synthetic fork oil on ester base which was developed for all forks of high performance motorbikes and especially for USD forks. The synthetic components and the excellent viscosity index of RAVENOL Fork Oil Light 5W offer an optimum damping behaviour at all temperatures as well as an excellent air separation behaviour under all operating conditions – even during racings.

Application directions:

RAVENOL Fork Oil Light 5W was developed for the use in all chassis components of two-wheeler vehicles and offers excellent power characteristics. In order to obtain the optimum viscosity for the vehicle and operating condition the fully synthetic fork oils are miscible among each other.

Quality classification:

RAVENOL Fork Oil Light 5W is practice-related and tested for the use in aggregates of: Yamaha, Kawasaki, Honda, Aprilia, BMW, Suzuki, Ducati, Triumph, Moto-Guzzi

Characteristics:

RAVENOL Fork Oil Light 5W offers:

- good damping characteristics at all temperatures
- a high and stable viscosity index
- an excellent protection against corrosion, therefore a longer endurance of the fork components
- as far as possible protection against corrosion of the inside components
- a very good air and water separation behaviour to prevent foam formation
- neutral behaviour against sealings made of plastics
- a very low pour point

Technical values:

<u>Characteris</u>	tics	unit	data	test according to
Colour			clear, green	
Density	at 15 ℃	g/ml	0,827	DIN 51 7 57
Viscosity	at -40 ℃	mPas	<1100	DIN 51 562
	at 40 ℃	mm ² /s	20,2	DIN 51 562
	at 100 ℃	mm ² /s	6,6	DIN 51 562
Flash poin	t COC	$\mathcal C$	150	DIN ISO 2592
Pour point		$\mathcal C$	<-50	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.