

Ravensberger Schmierstoffvertrieb GmbH  
Postfach 1163  
33819 Werther  
Tel.: 05203/9719-0  
Fax.: 05203/9719-40 / 41

- ProductInformation -

**RAVENOL Fork Oil Very Heavy 20W**

Art. 1182106

**Description:**

**RAVENOL Fork Oil Very Heavy 20W** is a fork oil on mineral oil base which was developed for all forks of off-road motorbikes and motor cross bikes.

**RAVENOL Fork Oil Very Heavy 20W** is especially characterised by a high and stable viscosity index as well as a solid corrosion protection. Efficient additives offer even under extreme loads an excellent corrosion protection. The behaviour against sealing materials is neutral.

**Application Directions:**

**RAVENOL Fork Oil Very Heavy 20W** was developed for the use in all chassis components of two-wheeler vehicles and offers good power characteristics. In order to obtain the optimum viscosity for the vehicle and operating condition the mineral fork oils are miscible among each other.

**Quality Classification:**

**RAVENOL Fork Oil Very Heavy 20W** is tried and tested for aggregates specifying:

**Recommendations:** Yamaha, Kawasaki, Honda, Aprilia, BMW, Suzuki, Ducati, Triumph, Moto-Guzzi

**Technical Characteristics:**

**RAVENOL Fork Oil Very Heavy 20W** offers:

- good damping characteristics at all temperatures
- a high and stable viscosity index
- an excellent protection against corrosion, therefore a longer endurance of the fork components
- as far as possible protection against corrosion of the inside components
- a very good air and water separation behaviour to prevent foam formation
- neutral behaviour against sealings made of plastics
- a very low pour point

**Technical Values:**

Characteristics	unit	data	test according to	
<b>Colour</b>		yellow brown	visual	
<b>Density</b>	at 20 °C	kg/m <sup>3</sup>	869	EN ISO 12185
<b>Viscosity</b>	at 40 °C	mm <sup>2</sup> /s	68,0	DIN 51 562
	at 100 °C	mm <sup>2</sup> /s	10,9	DIN 51 562
<b>Viscosity index</b>			151	DIN ISO 2909
<b>Flash point (COC)</b>	°C		230	DIN ISO 2592
<b>Pour point</b>	°C		-35	DIN ISO 3016
<b>TBN</b>	mg KOH/g		0,4	DIN ISO 3771
<b>Sulphated ash</b>	% wt.		approx. 0,06	

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.  
26.01.2015