Ravensberger Schmierstoffvertrieb GmbH Postfach 1163

33819 Werther

Tel.: 05203/9719-0 Fax.: 05203/9719-40 / 41

Certificate / ProductInformation-

RAVENOL ATF Dexron DII

Art. 1213102

Description:

RAVENOL ATF Dexron D II is a first class transmission fluid for automatic transmissions of all vehicles and working machines on the basis of high refined mineral oils with a corresponding additive treatment.

Application Directions:

RAVENOL ATF Dexron D II was developed for the use in automatic transmissions, hydro steering mechanisms, converters and power transmissions and can be used as a universal ATF (Automatic-Transmission-Fluid) for all vehicles and working machines.

Quality Classification:

RAVENOL ATF Dexron D II is approved, tried and tested for aggregates specifying:

GM Dexron®-IID

Allison C3/C4

<u>Approvals:</u> MB-Approval 236.7, ZF TE-ML 03D, 04D, 11A, 14A, 17C, VOITH H55.6335.xx <u>Recommendations:</u> MB 236.6, MAN 339 Typ Z-1, Ford SQM-9010B, Ford M2C-138 CJ, 166H, 185A, Cat-TO-2, MERCON, RENK DOROMAT, CVT

Technical Characteristics:

RAVENOL ATF Dexron D II offers:

- protection against corrosion, sludge and sticking
- an excellent and very shear stable viscosity temperature behaviour
- · no problems concerning very low respectively very high temperatures
- an excellent high thermal capacity
- · free of foam even under hardest loads
- neutral behaviour against sealing materials
- mixable and compatible with all kinds of ATF

Technical Values:

Characteristics		unit	data	test according to
Colour			red	visual
Density	at 20°C	kg/m³	866	DIN 51 757
Viscosity	at 40°C	mm²/s	35,0	DIN 51 562
-	at 100°C	mm²/s	7,2	DIN 51 562
Viscosity index VI			174	DIN ISO 2909
Flashpoint COC		°C	210	DIN ISO 2592
Pour point		°C	- 39	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.