Ravensberger Schmierstoffvertrieb GmbH Postfach 1163 33819 Werther

Tel.: 05203/9719-0 Fax.: 05203/9719-40 / 41

# Certificate / ProductInformation-

#### **RAVENOL MTF-3 SAE 75W**

Art. 1221104

Special Fluid

### **Description:**

**RAVENOL MTF-3 SAE 75W** is a fully synthetic low-viscosity transmission oil for special manual transmissions. **RAVENOL MTF-3 SAE 75W** is designed based on synthetic base oils and specially coordinated additive treatment. This exceeds the needs of today's application requirements.

**RAVENOL MTF-3 SAE 75W** is outstanding for use under severe mechanical and thermal stress on transmission oils, even with extended oil change intervals.

### **Application Directions:**

**RAVENOL MTF-3 SAE 75W** is a fully synthetic transmission oil for manual transmissions.

## **Quality Classification:**

RAVENOL MTF-3 SAE 75W is tried and tested for aggregates specifying:

## Recommendations:

- BMW 2300 7533 818 MTF LT-3 83 22 0 396 706 83 22 7 533 818 MTF LT-3
- MTF JWS2271
- PSA Standard 9730A8
- TOYOTA 08885-81001 08885-81081
- VOLVO 1161839 1161838
- VW/AUDI G 060726A2, G 052171A2, G 052512A2, VW G 070 726 A2
- FORD WSS-M2C200-D2

### **Technical Characteristics:**

### **RAVENOL MTF-3 SAE 75W** offers:

- A high pressure stable lubricating film even at high oil temperatures and under high stress.
- Outstanding shearing stability and excellent thermal stability.
- · Excellent viscosity-temperature properties.
- High oxidation stability.
- Excellent wear protection, outstanding EP properties.
- Low foaming properties even at high speeds.
- Good shifting behaviour even in low temperatures, extremely low pour point.
- Extended life.
- A stable lubricating film even at high oil temperatures and under high stress.

### **Technical Values:**

Characteristics		unit	data	test according to
Colour			brown	visual
Density	at 20°C	kg/m³	846	EN ISO 12185
Pour point		°Č	-60	<b>DIN ISO 3016</b>

All indicated data are approximate values and are subject to the commercial fluctuations.

RAVENOL special transmission fluid is special development for special gear and can not be selected on the basis of technical parameters (viscosity, etc.). Therefore the decision was made not to give technical data.

Please note: RAVENOL special transmission fluid is exclusively to apply under the original number, as indicated in the product information. Not sure of the correct transmission fluid, you can ask your garage or the car dealer with respect to the original OEM gear type and number or consult our advisers. It must be specified the VIN code (Vehicle Identification Number) of your vehicle.

Number) of your vehicle.

Misapplication of RAVENOL special transmission fluid can lead to malfunction of the transmission shifting problems, increased fuel consumption, unwanted slip behavior, etc. cause and cause the failure of the transmission.

Ravensberger Schmierstoffvertrieb GmbH does not liable for transmission failures in case of wrong selection of RAVENOL special transmission fluid.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems occur please consult a technician.