

- Certificate / ProductInformation -

**RAVENOL Getriebeoel LS SAE 75W-90**

Art. 1222102

**Description:**

**RAVENOL Getriebeoel LS SAE 75W-90** is a semi-synthetic lubricant for mechanical transmissions. **RAVENOL Getriebeoel LS SAE 75W-90** is designed based on high-quality solvent refined and synthetic base oils with special additive treatment and inhibition for higher stress on manual transmission oils and ensuring trouble-free transmission function.

**Application:**

**RAVENOL Getriebeoel LS SAE 75W-90** was developed specifically for use in differential gear units with limited slip. It also ensures trouble-free lubrication in self-locking, hypoid geared transmissions.

**Quality classification:**

**RAVENOL Getriebeoel LS SAE 75W-90** is tried and tested for aggregates specifying:

API GL-5

Recommendations: MIL-L-2105D, ZF TE-ML 05C/D

**Technical characteristics:**

**RAVENOL Getriebeoel LS SAE 75W-90** offers:

- excellent oxidation stability
- excellent protection against rust and corrosion
- prevents foaming
- outstanding extreme pressure properties
- excellent limited slip properties
- fuel savings

**Technical values:**

Characteristics	unit	data	test according to
<b>Colour</b>		yellow brown	visual
<b>Density</b> at 20°C	kg/m <sup>3</sup>	871	EN ISO 12185
<b>Viscosity</b> at 40°C	mm <sup>2</sup> /s	78,8	DIN 51 562
at 100°C	mm <sup>2</sup> /s	14	DIN 51 562
<b>Viscosity Index VI</b>		192	DIN ISO 2909
<b>Flash point</b> COC	°C	172	DIN ISO 2592
<b>Pour point</b>	°C	-40	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.