

Ravensberger Schmierstoffvertrieb GmbH  
Postfach 1163  
33819 Werther  
Tel.: 05203/9719-0  
Fax.: 05203/9719-40 / 41

- Certificate / ProductInformation -

**RAVENOL Hypoid EPX Getriebe-Oel SAE 85W-140 GL-5**

Art.1223211

**Description:**

**RAVENOL Hypoid EPX Getr.-Oel SAE 85W-140 GL-5** is a lubricating oil for mechanical gears based on high quality and solvent refined base oils. Special extreme pressure (EP)-active substances and selected additives give excellent lubricating oil properties.

**RAVENOL Hypoid EPX Getr.-Oel SAE 85W-140 GL-5** is designed for use with maximum duty, hypoid gearing gears (axel drive, manual transmission, etc.), so far extreme pressure gear oils are required.

**Application Directions:** **RAVENOL Hypoid EPX Getr.-Oel SAE 85W-140 GL-5** is used with maximum duty, hypoid gearing gears (axel drive, manual transmission, etc.).

**Quality Classification:**

**RAVENOL Hypoid EPX Getr.-Oel SAE 85W-140 GL-5** is tried and tested for aggregates specifying:

**Specifications:** API GL 5

**Recommendations:** MIL-L-2105 D, ZF TE-ML 05A, 16D, 21A, Ford M2C-9002A, MAN 342 Typ M-1, CS 3000B, Mack GO-G, GM

**Technical Characteristics:**

**RAVENOL Hypoid EPX Getr.-Oel SAE 85W-140 GL-5** offers:

- a very good oxidation stability
- widest possible protection against rust and corrosion
- no foam formation
- excellent extreme pressure properties
- low pour point
- neutral behaviour towards metals and sealing materials

**Technical Values:**

Characteristics		unit	data	test according to
<b>Colour</b>			brown	visually
<b>Density</b>	at 20°C	kg/m <sup>3</sup>	909	EN ISO 12185
<b>Viscosity</b>	at 40°C	mm <sup>2</sup> /s	340,0	DIN 51 562
	at 100°C	mm <sup>2</sup> /s	25,0	DIN 51 562
<b>Viscosity index VI</b>		--	96	DIN ISO 2909
<b>Flash point (COC)</b>		°C	245	DIN ISO 2592
<b>Pour point</b>		°C	- 15	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems occur please consult a technician.

28.01.15