

- ProductInformation-

RAVENOL Getriebeoel SLG SAE 80W-90

Art. 1223305

Description:

RAVENOL Getriebeoel SLG SAE 80W-90 is high quality multifunction gear oil, bases on high quality solvent refined base oils and special EP-additives.

Due to viscosity modification SAE 80W-90 **RAVENOL Getriebeoel SLG SAE 80W-90** offers a good after flow at low temperatures and a high shear stability at high temperatures.

Application directions:

RAVENOL Getriebeoel SLG SAE 80W-90 is high quality multifunction gear oil for manual transmissions and hypoid differentials in passenger cars, delivery vans and heavy trucks.

Quality classification:

RAVENOL Getriebeoel SLG SAE 80W-90 is approved and corresponds to:

API GL-4/GL-5, MT-1

MIL-L-2105 A/B/C/D/E

Approval: MAN 341 Typ E2

Specification: MAN 3343 Typ M (prolonged Oildrain intervals), ZF-TE-ML 02B, 05A, 12E, 16B, 17B, 19B, 21A, SCANIA STO 1:0, VOLVO 97310

Characteristics:

RAVENOL Getriebeoel SLG SAE 80W-90 offers:

- An excellent thermal stability
- Excellent extreme pressure properties
- A good circuit behavior at low temperatures
- An extended service life
- Neutral behavior towards sealing materials
- Reliable protection against wear, sludge, adhesion and corrosion

Technical values:

Characteristics		unit	data	test according to
Colour			brown	
Density	at 20°C	g/ml	0,889	EN ISO 12185
Viscosity	at 40°C	mm ² /s	146,4	DIN 51 562
	at 100°C	mm ² /s	15,2	DIN 51 562
Viscosity Index VI			105	DIN ISO 2909
Flash point (COC)		°C	168	DIN ISO 2592
Pour point		°C	-31	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.