

Ravensberger Schmierstoffvertrieb GmbH  
Postfach 1163  
33819 Werther  
Tel.: 05203/9719-0  
Fax.: 05203/9719-40 / 41

**- Certificate / ProductInformation -**

**RAVENOL MARINE Gear Lube**  
Art. 1233100

**Description:**

**RAVENOL MARINE Gear Lube** contains high-quality base oils, with a balanced combination of additives. This guarantees a high load carrying capacity, wear protection and oxidation stability.

Because of the balanced additive combination good viscosity-temperature behavior, low pour point and suppression of foam formation allows use with different operating conditions.

**Application directions:**

**RAVENOL MARINE Gear Lube** is gear oil for lubricating when GL-5 transmission types are required.

**Quality classification:**

**RAVENOL MARINE Gear Lube** is tried and tested for aggregates specifying:

API GL-5

OMC, VOLVO PENTA, Mercruiser, YANMAR

**Characteristics:**

**RAVENOL MARINE Gear Lube** offers:

- Good adhesion and pressure-resistant lubricating film
- Excellent oxidation stability
- Very good viscosity-temperature behaviour
- Wear-resistant effect
- No foaming tendency
- A neutral behaviour towards metals and sealing materials

**Technical values:**

Characteristics	unit	data	test according to
<b>Colour</b>		blue	
<b>Density</b>	at 20 °C	kg/m <sup>3</sup>	888
<b>Viscosity</b>	at 40 °C	mm <sup>2</sup> /s	150,5
	at 100 °C	mm <sup>2</sup> /s	15,2
<b>Viscosity index</b>			102
<b>Flash point</b>	COC	°C	210
<b>Pour point</b>		°C	- 27

All indicated data are approximate values and are subject to the commercial fluctuations.