Ravensberger Schmierstoffvertrieb GmbH Postfach 1163

Postfach 1163 33819 Werther

Tel.: 05203/9719-0 Fax.: 05203/9719-40 / 41

- Certificate / Product Information -

RAVENOL Hydraulikoel TS 32 (HLP)

Art. 1323104

Description:

RAVENOL Hydraulikoel TS 32 (HLP) is optimal alloyed mineral hydraulic oil with a high performance level and a wide application area of the whole industry. It is characterised by good viscosity temperature behaviour, a high aging resistant and a solid corrosion protection. Efficient additives offer an excellent corrosion protection even under extreme loads. The behaviour of sealing materials is neutral.

Application directions:

RAVENOL Hydraulikoel TS 32 (HLP) is for universally use in all hydraulic systems. It is recommended in high performance hydraulic systems with high pressure pumps of all types, in sensitive control systems, for hydraulic systems in agriculture, to supply small gearboxes and for use in circulating systems.

Quality Classification:

RAVENOL Hydraulikoel TS 32 (HLP) is tried and tested for aggregates specifying:

<u>Specifications</u>: DIN 51 502 HLP, DIN 51 524, part 2 FZG-Test A 8,3/90: 12th load level is reached. Recommendation: Voith Oillist 3626-011000de

Characteristics:

RAVENOL Hydraulik TS 32 (HLP) offers:

- a high performance level
- a very good viscosity temperature behaviour
- a high aging resistant
- an excellent corrosion protection
- a solid corrosion protection
- neutrality of sealing materials

Technical values:

Characteristics		unit	data	test according to
Colour			yellow-brown	visual
Density	at 20 °C	kg/m³	856	EN ISO 12185
Viscosity	at 40 °C	mm²/s	33,2	DIN 51 562
-	at 100 °C	mm²/s	5,8	DIN 51 562
Viscosity index			120	DIN ISO 2909
Flash point	COC	°C	220	DIN ISO 2592
Pourpoint		°C	- 30	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.