

Ravensberger Schmierstoffvertrieb GmbH
Postfach 1163
33819 Werther
Tel.: 05203/9719-0
Fax.: 05203/9719-40 / 41

- ProductInformation -

RAVENOL Turbinenöl T 46

Art. 330355

Description:

RAVENOL Turbinenöl T 46 is produced for the lubrication of gas and steam turbines as well as turbo compressors with and without transmission according to the specifications of DIN 51 515-2.

RAVENOL Turbinenöl T 46 is based on high quality mineral base oils with agents to increase the corrosion protection and aging resistance.

Application directions:

RAVENOL Turbinenöl T 46 is used in fixed gas and steam turbines as well as electrical machines or machines driven by steam turbines like generators, compressors, pumps and transmissions.

RAVENOL Turbinenöl T 46 can also be used for the lubrication of hydraulic systems, compressors, gear transfers and bearings in case of problems of the contamination with water because a high protection against rust and oxidation is requested.

Quality classification:

RAVENOL Turbinenöl T 46 corresponds to the following specifications respectively classifications:

BS 489

DIN 51515 (L-TD)

ISO 6743/0

Characteristics:

RAVENOL Turbinenöl T 46 is a universal mineral oil for turbines of especially chosen refined base oils with a natural high viscosity index. So-called "metal deactivators" are added to the turbine oil in addition to the normal additives in order to guarantee the following characteristics:

- an excellent thermic and oxidative stability
- an excellent viscosity temperature behaviour
- a high and stable viscosity index
- a very good oxidation stability also at very high temperatures
- a good protection against corrosion of Ferro and non Ferro metals
- an excellent water separation behaviour
- a very good air separation behaviour which excludes foam formation as far as possible
- a low pour point
- a good corrosion behaviour
- an excellent water separation behaviour / demulsifying behaviour

Technical values:

Characteristics	unit	data	test according to
Density at 20 °C	g/ml	0,873	DIN 51 7 57
Viscosity at 40 °C	mm ² /s	46	DIN 51 562
at 100 °C	mm ² /s	6,7	DIN 51 562
Viscosity index		98	DIN ISO 2909
Flash point COC	°C	215	DIN 51 376
Pour point	°C	- 30	DIN 51 597
TBN	mg KOH/g	0,15	DIN ISO 3771

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

11.11.2008