

Ravensberger Schmierstoffvertrieb GmbH
P.O. Box 1163
33819 Werther
Tel: 05203/9719-0
Fax: 05203/9719-40 / 41

- Certificate / Product information-

RAVENOL Petrol Performance Optimizer Premium

Art. 1390201

Premium fuel additive for all petrol engines

Petrol additive

Description:

RAVENOL Petrol Performance Optimizer Premium is a premium fuel additive for all petrol engines for cleaning all components in contact with fuel. Ensures a technically safe and economic operation.

RAVENOL Petrol Performance Optimizer Premium provides a verifiable saving of fuel, a higher octane rating and increased performance.

RAVENOL Petrol Performance Optimizer Premium reduces NOx emissions, which is tested and certified by the TÜV (Technical Inspection Agency) Thuringia.

RAVENOL Petrol Performance Optimizer Premium guarantees ideal combustion. This prevents deposits and oxidation by-products on fuel lines, injection needles, cylinders, spark plugs and combustion chamber.

RAVENOL Petrol Performance Optimizer Premium prolongs the service life of catalytic converters and lambda probes by means of optimum combustion.

Application Directions:

RAVENOL Petrol Performance Optimizer Premium is added to the petrol.

Area of application:

- Petrol-operated engines
- Can be used preventively at every service
- In the event of increased fuel consumption
- In cases where inadequate fuel is suspected
- When using E10 petrol blend
- Also recommended for direct injection engines

Application: Pour the contents of the container into the tank. Fuel volume up to 60 l of petrol. Minimum fuel capacity according to volume of fuel reserve.

Quality Classification:

RAVENOL Petrol Performance Optimizer Premium is an easy to mix petrol additive.

The efficacy of the NOx reduction is tested and certified by the TÜV (Technical Inspection Agency) Thuringia.

Technical Characteristics:

RAVENOL Petrol Performance Optimizer Premium provides:

- Certified efficacy of the NOx reduction by the TÜV (Technical Inspection Agency) Thuringia
- guarantees optimum combustion
- Saving of fuel
- Cleaning of fuel lines, injection needles, cylinders, spark plugs and combustion chamber. Increases octane rating and performance.
- Prolongs the service life of catalytic converters and lambda probes

Technical Values:

Characteristics	unit	data	test according to
Colour		yellow	visual
Density at 20°C	kg/m ³	790	EN ISO 12185
Viscosity at 40°C	mm ² /s	7	DIN EN ISO 3104
Flash point (PM)	°C	15	DIN ISO 3679

All indicated data are approximate values and are subject to the commercial fluctuations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems occur please consult a technician.

22.09.15