

Ravensberger Schmierstoffvertrieb GmbH
P.O. Box 1163
33819 Werther
Tel: 05203/9719-0
Fax: 05203/9719-40 / 41

- Certificate / Product information-

RAVENOL Diesel Quality Stabilisator

Art. 1390244

Fuel additive for all diesel engines

Diesel additive

Description:

RAVENOL Diesel Quality Stabilisator contains an innovative ingredient, which ensures the general quality of the fuel in diesel fuels.

RAVENOL Diesel Quality Stabilisator improves the storage stability of diesel fuels using effective antioxidants and dispersants.

RAVENOL Diesel Quality Stabilisator enables excellent oxidation protection even at higher temperatures.

RAVENOL Diesel Quality Stabilisator prevents smoke generation and bad smells.

Application Directions:

RAVENOL Diesel Quality Stabilisator is added to the diesel fuel.

Area of application:

- Diesel engines in passenger cars and lorries
- Ensures the quality of the fuel
- For vehicles with longer standstill periods
- Increases the storage stability regarding oxidation and biological contamination

Application: Pour the contents of the container into the full tank. The ideal dosage is a can of **RAVENOL Diesel Quality Stabilisator** per 40 litres of diesel.

Note: fill the tank completely if the vehicle has not been used for a longer period of time.

Quality Classification:

RAVENOL Diesel Quality Stabilisator increases the storage stability regarding oxidation and biological contamination using effective antioxidants.

Technical Characteristics:

RAVENOL Diesel Quality Stabilisator provides:

- Improved storage stability of the diesel fuel
- Prevention of microbiological contamination
- Protection against corrosion and deposits in the system
- Improved engine operation and acceleration performance at low outside temperatures
- Prevention of damages to fuel injection system caused by deposits
- Improved winter performance of the fuel

Technical Values:

Characteristics	unit	data	test according to
Colour		yellow	visual
Density at 20°C	kg/m ³	850	EN ISO 12185
Viscosity at 40°C	mm ² /s	7	DIN EN ISO 3104
Flash point (PM)	°C	65	DIN ISO 3679

All indicated data are approximate values and are subject to the commercial fluctuations.