

Ravensberger Schmierstoffvertrieb GmbH  
P.O. Box 1163  
33819 Werther  
Tel: 05203/9719-0  
Fax: 05203/9719-40 / 41

## - Certificate / Product information-

### RAVENOL Professional Radiator Stop Leak

Art. 1390301

Sealant for the cooling system

Radiator additive

#### Description:

**RAVENOL Professional Radiator Stop Leak** is a dispersion for protecting the cooling system and the combustion chamber against leaks and increasing operational safety.

**RAVENOL Professional Radiator Stop Leak** permanently seals hairline cracks and leaks.

**RAVENOL Professional Radiator Stop Leak** prevents seals from sweating and the loss of coolant.

**RAVENOL Professional Radiator Stop Leak** is suitable for closed cooling systems.

#### Application Directions:

**RAVENOL Professional Radiator Stop Leak** is added to the radiator. If there are filters in the cooling system, a radiator jointing material may not be used.

#### Area of application:

- Severe sweating of cylinder head gaskets
- Leaky hose connections
- Hairline cracks in the radiator, cylinder head or engine block

Application: **RAVENOL Professional Radiator Stop Leak** suffices for 10 litres of coolant. Open the heating valve completely. The engine should be at operating temperature.

Shake the can and fill the content into the cooling system with the engine running. Add coolant.

After filling, allow the engine to continue to run for at least 10 min. or take a test drive. Check the system's coolant level, absence of air and leak tightness.

For truck radiators mix ratio max. 1:100.

**RAVENOL Professional Radiator Stop Leak** is also suitable for closed cooling systems.

#### Quality Classification:

**RAVENOL Professional Radiator Stop Leak** is completely compatible with anti-freeze agents and coolants.

**RAVENOL Professional Radiator Stop Leak** is neutral in regard to rubber, synthetic materials, light alloys and non-ferrous metals.

#### Technical Characteristics:

**RAVENOL Professional Radiator Stop Leak** provides:

- Protection against sweating cylinder head gaskets
- Sealing of hairline cracks and leaks in the cooling system

#### Technical Values:

Characteristics	unit	data	test according to
<b>Aroma</b>		citrus	
<b>Colour</b>		green blue	visual
<b>Density</b>	at 20°C	1020	EN ISO 12185
<b>pH-Value</b>	at 20°C	9.5	DIN 19268

All indicated data are approximate values and are subject to the commercial fluctuations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems occur please consult a technician.

22.09.15