

Ravensberger Schmierstoffvertrieb GmbH  
P.O. Box 1163  
33819 Werther  
Tel: 05203/9719-0  
Fax: 05203/9719-40 / 41

## - Certificate / Product information-

### RAVENOL Professional Radiator Stop Cleaner

Art. 1390302

Cleaning additive for all radiators

Radiator additive

#### Description:

**RAVENOL Professional Radiator Cleaner** is a radiator cleaning additive, which is used for the quick and easy cleaning of the cooling and heating system.

**RAVENOL Professional Radiator Cleaner** breaks down and binds greasy and oily deposits in radiators, heating systems and pipelines.

**RAVENOL Professional Radiator Cleaner** infiltrates and eliminates sludge and corrosion deposits.

**RAVENOL Professional Radiator Stop Cleaner** neutralises lime residue.

#### Application Directions:

**RAVENOL Professional Radiator Cleaner** is added to the radiator. It is recommended to replace rubber parts affected by oil seepage.

#### Area of application:

- Radiator repairs
- In the event of reduced radiator performance
- In the event of deposits in the cooling system
- Changing coolant
- For cleaning purposes after engine repairs due to oil in the cooling system

Application: **RAVENOL Professional Radiator Cleaner** suffices for up to 10 litres of coolant.

Drain contaminated coolant before cleaning and fill up with fresh water.

Fill in **RAVENOL Professional Radiator Cleaner** and allow the engine to run at operating temperature for approx. 30 minutes. Drain contaminated mixture – in the case of severe contamination, repeat treatment if necessary. Rinse cooling system with clear water. Refill and remove air after cleaning the cooling system and check for leak tightness.

#### Quality Classification:

**RAVENOL Professional Radiator Cleaner** can lead to an improved cooling performance after repairs on the cooling system.

#### Technical Characteristics:

**RAVENOL Professional Radiator Cleaner** offers:

- Cleaning of the cooling and heating system
- Protection of the new coolant against prior contamination
- Elimination of sludge and corrosion residue

#### Technical Values:

Characteristics		unit	data	test according to
<b>Colour</b>			colourless	visual
<b>Density</b>	at 20°C	kg/m <sup>3</sup>	1003	EN ISO 12185
<b>pH-value</b>	at 20°C		10.25	DIN 19268

All indicated data are approximate values and are subject to the commercial fluctuations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems occur please consult a technician.

22.09.15