

Ravensberger Schmierstoffvertrieb GmbH
Postfach 1163
33819 Werther
Tel.: 05203/9719-0
Fax.: 05203/9719-40 / 41

- Certificate / ProductInformation -

RAVENOL RFS SAE 15W50

Art. 1142105

RACING

Description:

RAVENOL RFS SAE 15W50 is a semi-synthetic multigrade engine oil based on esters and poly-alpha olefins. Suitable for use in modern gasoline engines at car race even under difficult conditions. Due to its high viscosity index, it's good shear stability and a highly effective special additives **RAVENOL RFS SAE 15W50** formula is also suitable for extremely sporty driving style. Increased protection against wear, corrosion (oxidation) and foaming.

Application Directions:

RAVENOL RFS SAE 15W50 is used as special oil for car racing such as DMV Tourenwagen Challenge even under difficult conditions.

Quality Classification:

RAVENOL RFS SAE 15W50 is tried and tested for aggregates specifying:

Spezification: API SN/CF, ACEA A3/B4

Recommendation: MB 229.1

Technical Characteristics:

RAVENOL RFS SAE 50 offers:

- The prevention of sludge formation
- A very high viscosity index
- A very good cold start characteristics
- Low friction loss therefore little wear
- Natural oxidation stability
- Very low evaporation

Technical Values:

Characteristics	unit	data	test according to	
Colour		brown	visual	
Density	at 20°C	kg/m ³	873	DIN 51 757
Viscosity	at -20°C	mPa*s	4800	ASTM D 5293
	at 40°C	mm ² /s	131,0	DIN 51 562
	at 100°C	mm ² /s	17,1	DIN 51 562
Viscosity index VI		143	DIN ISO 2909	
Flash point (COC)	°C	226	DIN ISO 2592	
Pour point	°C	- 27	DIN ISO 3016	

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

27.06.14