

Ravensberger Schmierstoffvertrieb GmbH  
Postfach 1163  
33819 Werther  
Tel.: 05203/9719-0  
Fax.: 05203/9719-40 / 41

- ProductInformation -

**RAVENOL MARINEOIL PETROL SAE 15W-40**

Art. 163200

**Description:**

**RAVENOL MARINEOIL PETROL SAE 15W-40** is a high additive treated HD engine oil for marine gasoline engines.

**RAVENOL MARINEOIL PETROL SAE 15W-40** is especially produced for extended oil change intervals (under consideration of the manufacturer instruction).

**Quality classification:**

**RAVENOL MARINEOIL PETROL SAE 15W-40** corresponds to the specifications for 4 stroke petrol marine engines :

API SL

Approvals : VOLVO Penta AB, Mercruiser, Yanmar, Kohler

**Technical characteristics:**

**RAVENOL MARINEOIL PETROL 15W-40** offers :

- an extreme high pressure absorption capacity
- a very high oxidation stability
- an excellent aging resistance
- an excellent viscosity temperature behaviour
- high safety reserves also under boundary lubrication conditions
- suitability for extended oil change intervals
- suitability for complicate operating conditions

**Technical values:**

Characteristics		unit	data	test according to
<b>Colour</b>			blue	
<b>Density</b>	at 20 °C	g/ml	0,885	DIN 51 7 57
<b>Viscosity</b>	at 40 °C	mm <sup>2</sup> /s	106,0	DIN 51 562
	at 100 °C	mm <sup>2</sup> /s	14,5	DIN 51 562
<b>Viscosity index</b>			144	
<b>Flash point</b>	COC	°C	222	DIN ISO 2592
<b>Pour point</b>		°C	- 27	DIN ISO 3016
<b>TBN</b>		mg KOH/g	11,5	DIN ISO 3771
<b>Sulfat ash</b>		%	1,3	DIN 51 575

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

11.11.2008