

- Certificate / ProductInformation -

**RAVENOL ATF Fluid**

Art. 1213101

**Description:**

**RAVENOL ATF Fluid** is a high quality transmission fluid formulated with a blend of refined base oils with special additives and inhibitors to ensure smooth and efficient operation of the transmission.

**Application Directions:**

**RAVENOL ATF Fluid** is designed for automatic fluid couplings, torque converters, servo steering systems and other hydrostatic and hydrodynamic systems for which an ATF of Type A Suffix A specification is required.

**RAVENOL ATF Fluid** is not suitable for use where DEXRON ATF Type B, DEXRON ATF Type D or Ford specification M2C-33 E / F / G are explicitly required in the filling instructions!

**Quality Classification:**

**RAVENOL ATF Fluid** is tried and tested for aggregates specifying:

**Recommendations:** Type A Suffix A (TASA), ALLISON C-4, MAN 339 Typ A, MB 236.2, Renk Doromat, Cat. TO-2

**Technical Characteristics:**

**RAVENOL ATF Fluid** offers:

- Exceptionally good resistance to aging
- A very good viscosity-temperature behaviour
- Effective protection against wear
- Very good oxidation stability and low foaming tendency
- Enhanced protection against corrosion
- An extremely low pour point
- Compatible with all types of sealing materials
- Miscibility and compatibility with all brands of ATF's with Type A Suffix A specification

**Technical Values:**

Characteristics	unit	data	test according to	
<b>Colour</b>		red	visual	
<b>Density</b>	at 20°C	kg/m <sup>3</sup>	866	DIN 51 757
<b>Viscosity</b>	at 40°C	mm <sup>2</sup> /s	35,0	DIN 51 562
	at 100°C	mm <sup>2</sup> /s	7,2	DIN 51 562
<b>Viscosity index VI</b>			174	DIN ISO 2909
<b>Flashpoint COC</b>	°C		210	DIN ISO 2592
<b>Pour point</b>	°C		- 42	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.