

Ravensberger Schmierstoffvertrieb GmbH  
Postfach 1163  
33819 Werther  
Tel.: 05203/9719-0  
Fax.: 05203/9719-40 / 41

**- Certificate / ProductInformation -**

**RAVENOL DOT 4**

Art. 1350601

**Description:**

**RAVENOL DOT 4** is a brake fluid for the use in all vehicles with optimum ABS characteristics. There is a chemical stability and it is provided with additives which save the best lubrication efficiency. Because of the special formulation of **RAVENOL DOT 4** the international specifications SAE J1704, ISO 4925 and the safety regulations FMVSS 116 DOT3 and DOT4 from the United States of America are exceeded.

**Application Directions:**

**RAVENOL DOT 4** can be used in all vehicles for which the DOT 4 specification for brake fluids is required. It is suitable for all hydraulic brake systems with synthetic fluids.

**RAVENOL DOT 4** is miscible with all known brake fluids of the same specification.

**Quality Classification:**

**RAVENOL DOT 4** is tried and tested for aggregates specifying:

SAE J1704

ISO 4925

FMVSS 116 DOT4

**Technical Characteristics:**

**RAVENOL DOT 4** offers:

- optimum ABS characteristics
- chemical stability
- best lubrication efficiency
- neutral behaviour regarding brake parts
- low viscosity at low temperatures
- miscible with all brake fluids of the same specifications

**Technical Values:**

Characteristics	unit	data	test according to
<b>Boiling point</b>	°C	min. 260	ISO 4925
<b>Wet boiling point</b>	°C	min. 165	ISO 4925
<b>Viscosity</b> at -40°C	mm <sup>2</sup> /s	max. 1500	DIN EN ISO 3104

All indicated data are approximate values and are subject to the commercial fluctuations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems occur please consult a technician.

19.03.14